

armstrong optical

EasIR-2 handheld thermography camera



The ruggedized, robust and high performance thermography camera is opening new markets in industrial temperature measurement. The ergonomic design enables single-handed operation with a one-button shoot-and-save capability.

The built-in visible camera enables Picture-in-Picture and IR-Fusion display allowing fast and reliable trouble-shooting of electrical installations, electro-mechanical equipment, process systems, HVAC equipment and building inspection.

Thermal:		Visible:	
Detector type	Uncooled FPA	Camera	CMOS
Spectral range	8 - 12 μ m	Sensor size	2Mpixel
Sensor size	160x120 pixels	Display	3.6" TFT high res LCD
Sensitivity	≤ 0.1 °C @ 30 °C	T range	-20 °C to +250 °C (+350 °C option)
Field of view	20.6° x 15.5°	Accuracy	± 2 °C or $\pm 2\%$ of reading
Focal length	11mm	Measurement modes	Spot, PIP, IR fusion etc
Image display	6 colour palettes	Laser locator	diode laser
Focus	motorised		

Image storage:		System status:	
Type	2Gb mini SD card	LCD display	Battery indicator
File format	JPEG (1000 images)	Sound	Auto for power level

Power:		Interfaces:	
Power supply	110/240V AC adaptor	USB2.0	Image transfer to PC
Battery	AA alkaline	Video	PAL/NTSC
Operating duration	~3hrs continuous		

Environmental specification:		Physical:	
Operating temperature	0 °C to +50 °C	Size	111 x 124 x 240mm
Storage temperature	-20 °C to +60 °C	Weight	0.73kg (inc. batteries)
Humidity	10-95% N/C	Tripod mounting	1/4" - 20 (option)
Encapsulation	IP54 / IEC529		

Armstrong Optical Ltd, 31 Caxton House, Northampton Science Park, Northampton, United Kingdom NN3 6LG

Tel: +44 (0) 1604 654220, E: info@armstrongoptical.co.uk, W: www.armstrongoptical.co.uk