

armstrong optical

Thermal Camera IR110

By using an uncooled microbolometer array as its high-resolution sensor the IR110 Thermal Camera allows easy detection of objects in complete darkness and without the requirement of external illumination.

The special waterproof design and small size ensures the facile integration of the IR110 into, for instance, existing outdoor CCTV security systems to enable detection of intruders even on the darkest nights with no active illumination or artificial lighting.

With a choice of standard lenses ranging from 19mm f/0.7 right through to 140mm f/1.0 the IR110 can be tailored to most surveillance applications.



Versatile & portable

- The compact and portable design makes it perfectly suited to either mobile or fixed, day or night detection and surveillance.

Crisp & sharp imaging

- With a thermal sensitivity of 100mK, the camera is able to detect and capture extremely small temperature differences in high-resolution, crisp 16-bit thermal images. Automatic non-uniformity calibration at regular intervals keeps image noise-free even after extended operation.

Plug-and-play compatibility

- Standard video, power and serial communication interfaces enable the camera to work with standard video displays, external power supplies and remote control keyboards. There is no need to invest in a different infrastructure.

License free & rapid delivery

- Since the system utilises a European microbolometer FPA detector, the camera is without export or import license restriction, which significantly improves delivery time to our customers.



System Specification

Detector type:	Uncooled FPA microbolometer 160x120 pixel
Spectral range:	8 - 14 μm
Field of view:	17 x 13 degrees (with standard 19mm f/0.7 lens)
Thermal sensitivity:	0.1°C at 30°C
Start-up time:	<30sec
Gain & offset:	Auto or manual control
Electronic zoom:	x2, x4 interpolating
Contrast/brightness:	Auto or manual control
Control Interface:	RS232

Image presentation

Video output:	PAL/NTSC (PAL/NTSC to USB2.0 option)
Image colour:	B&W, W&B, multiple colours (9 palettes available)

Power system

Voltage requirement:	7 – 9 V DC
Power consumption:	3.5W typical

Environmental specification

Operating temperature:	-20 to +50°C
Storage temperature:	-40 to +60°C
Humidity:	Operation & storage 10-95%, non-condensing

Physical characteristics

Weight:	360gm
Dimensions:	117 x 64 x 64mm (without lens)
Tripod mount:	1/4" – 20

armstrong optical

Armstrong Optical Ltd., 31 Caxton House, Northampton Science Park, Northampton NN3 6LG, United Kingdom
Tel: +44 (0) 1604 654220 Fax: +44 (0) 1604 654221, Email: info@armstrongoptical.co.uk
Website: www.armstrongoptical.co.uk